

GREASE DISTRIBUTION




**AUTOMATIC
LUBE SYSTEMS**

AUTOMATIC LUBE SYSTEMS, INC.

WWW.AUTOMATICLUBESYSTEMS.COM

PHONE: 844-LUBE-SYS OR 844-582-3797

SALES@AUTOMATICLUBESYSTEMS.COM





AIR-OPERATED GREASE PUMP

pag. 4



FRAME RAM

pag. 8



PNEUMATIC GREASE PUMP SET

pag. 10



MANUAL GREASE PUMP

pag. 15



GREASE CONTROL VALVE / GREASE GUN

pag. 21



HOSE REELS / HOSE

pag. 24



FOLLOWER PLATE / DRUM COVER

pag. 29



HOSE REEL ACCESSORIES

pag. 31

The new air-operated grease pumps patented, fully designed and manufactured by WOLFLUBE, shows remarkable operating features. It is fully machined with electronic machine tools, the assembly is made with great care and the parts have been carefully tested in order to assure the best guarantee of reliability and a long life. The choice of materials and manufacturing quality make this pump suitable to work in the worst environmental conditions.

- **Brand new fully air operated motion reverse device, without cams and springs**
- **Reduced number of moving parts**
- **Large quantity of grease supplied at low air consumption**
- **High operating pressure**
- **Aluminum alloy body pump with electrolytic treatment that ensures very high corrosion strength**



AIR-OPERATED GREASE PUMPS



152801



Air-operated grease pump ratio=60:1

For standard pails 40 - 65 lbs

(shank length 18.89in)

Polyurethane seals

152805




Air-operated grease pump ratio=60:1


For standard kegs 120 lbs

(shank length 29.52in)

Polyurethane seals



152801	11.55	0.35	1
152805	13.89	0.46	1



Technical data		152801	152805
Compression ratio		60:1	60:1
Max pressure feedin	psi	116	116
Air consumption medium	gal/min	34.32	34.32
Air inlet connection	NPTF	1/4in	1/4in
Grease outlet connection	NPTM	1/4in	1/4in
Grease delivery capacity 87 psi	lbs/min	3.53	3.53
Noise	dB	76	76
Shank diameter	in	1.18	1.18
Shank length	in	18.90	29.52
For drums with capacity of	lbs	45 - 60	120

Those are suitable for the supply at high pressure of all kinds of grease at short and long distance.

The operating pressure of the grease pumps hereby may vary between a minimum of 36 psi and a maximum of 116 psi. In order to optimize the efficiency and the life of our air operated pumps, we recommend to use filtered and lubricated air.

152802



Air-operated grease pump ratio=60:1

For standrad drums 400 lbs

(shank length 37.40in)

Polyurethane seals

152803




Air-operated grease pump ratio=70:1


For standrad drums 400 lbs

(shank length 37.40in)

Polyurethane seals



152802	15.66	0.57	1
152803	15.66	0.57	1



Technical data		152802	152803
Compression ratio		60:1	70:1
Max pressure feedin	psi	116	116
Air consumption medium	gal/min	34.32	39.60
Air inlet connection	NPTF	1/4in	1/4in
Grease outlet connection	NPTM	1/4in	1/4in
Grease delivery capacity 87 psi	lbs/min	3.53	2.43
Noise	dB	76	76
Shank diameter	in	1.18	1.18
Shank length	in	37.40	37.40
For drums with capacity of	lbs	400	400



Those are suitable for central supply of plants where a major quantity of grease and a major pressure at long and short distance are required. The operating pressure of the grease pumps hereby may vary between a minimum of 36 psi and a maximum of 116 psi. In order to optimize the efficiency and the life of our pumps we recommend to use filtered and lubricated air.



152804





Air operated industrial pump for grease ratio=50:1

For standard drum 400 lbs

(shank length 37.40in)

Polyurethane seals

For high viscosity grease and oils



152804

46.31

2.47

1

Technical data		152804
Compression ratio		50:1
Max pressure feedin	psi	116
Air consumption medium	gal/min	0.46
Air inlet connection	NPTF	1/4in
Grease outlet connection	NPTM	1/4in
Grease delivery capacity 87 psi	lbs/min	9.92
Noise	dB	76
Shank diameter	in	1.77
Shank length	in	37.01
For drums with capacity of	lbs	400

Suitable for high pressure transfer of high viscosity grease and fluids over short and long distances and for central distribution plants with multiple distribution points. The operating pressure of the pumps may vary between a minimum of 44 psi and a maximum of 116 psi. To optimize the efficiency and the live in time of our air operated pumps Wolflube recommend to use filtered and lubricated air.

150205



Frame RAM for drum 400 lbs

Equipped with follower plate for grease pumps with shank Ø 1.18in

150206



Frame RAM for drum 400 lbs

Equipped with follower plate for grease pumps with shank Ø 1.77in

150207



Frame RAM for drum 400 lbs

Equipped with follower plate for grease pumps with shank Ø 1.97in

150208



Frame RAM for drum 400 lbs

Equipped with follower plate for grease pumps with shank F2in

Maximum height	Minimum height	Maximum pressure	Pushing power	For drum	Viscosity
			58 psi - 992 lbs		
110.31in	70.94in	116 psi	87 psi - 1433 lbs	260 - 485 lbs	200 - 500
			116 psi - 1918 lbs		ASTM (77°F)



150205	463.05	65.70	1
150206	463.05	65.70	1
150207	463.05	65.70	1
150208	463.05	65.70	1

Air operated two columns RAM and press for grease and viscous medias.

With its particular 3 ways control valve it lifts or pull down the pump and the follower plate, improving the exchanging effort of **396 - 485 lbs** (400 lbs) drum.

It is particularly advised for the use with high viscosity grease and medias (from 200CPS to 500ASTM).

The follower plate is pushed down by the pressurised pneumatic cylinders, avoiding rease flow interruptions by air pockets in the grease bed.

More over, it allows to collect all the grease from the inner walls down to the bottom of the drum, Pump suction is assisted.

Aluminium follower plate with rubber double ring Ø 23.03in
for drum 400 lbs

150209



with adaptor lange for Ø 1.18in shank

150210



with adaptor lange for Ø 1.77in shank

150211



with adaptor lange for Ø 1.97in shank

150212



with adaptor lange for F 2in shank



150209	54.46	2.47	1
150210	54.46	2.47	1
150211	54.46	2.47	1
150212	54.46	2.47	1

Aluminium casted follower plate for grease and viscous medias with rubber double ring Ø 23.03in for drum 400 lbs suitable for air operated grease pumps.

Equipped with ball valve, breather valve and adaptor.

TO ORDER: CALL 844-LUBE-SYS OR 844-582-3797

WWW.AUTOMATICLUBESYSTEMS.COM SALES@AUTOMATICLUBESYSTEMS.COM



150214

150213



Kit pump and RAM and press for grease for drum 400 lbs

Delivery 22.05 lbs/min

Composed by:

150203 Pump frame lifter and press 2 columns + follower plate

151019 Industrial air operated pump ratio=40:1

151017 Rubber hose R6 3/8in NPTF - NPTF 3/8in 3 ft length

151018 Rubber hose R6 1/2in NPTF - NPTF 1/2in 3 ft length

150214



Kit pump and RAM and press for grease for drum 400 lbs

Delivery 9.92 lbs/min

Composed by:

150202 Pump frame lifter and press 2 columns + follower plate

151020 Industrial air operated pump ratio=50:1

151017 Rubber hose R6 3/8in NPTF - NPTF 3/8in 3 ft length

151018 Rubber hose R6 1/2in NPTF - NPTF 1/2in 3 ft length

150215



Kit pump and RAM and press for grease for drum 400 lbs

Delivery 15.44 lbs/min

Composed by:

150203 Pump frame lifter and press 2 columns + follower plate



151021 Industrial air operated pump ratio=70:1

151017 Rubber hose R6 3/8in NPTF - NPTF 3/8in 3 ft length

151018 Rubber hose R6 1/2in NPTF - NPTF 1/2in 3 ft length



150213	509.36	67.11	1
150214	503.84	67.11	1
150215	513.77	67.11	1



- 1 Outlet feeding pump air
- 2 Off position
- 2A Lifting position up pump and follower plate
- 2B Acting position down press-fluid

- 3 Pressure regulator with manometer for feeding lifter air
- 4 Outlet feeding air lifter follower plate
- 5 Inlet feedineneral air into filter end lubricator

150301



Pneumatic wheeled grease pump for 35 lbs

Composed by:

Wheeled tank for 35 lbs



152806 Grease pump ratio=60:1

151001 Follower plate Ø 8.66in

150901 R2 1/4in hose - 10 ft length

100903 Grease gun with swivel joint

			
150301	39.25	0.35	1



150301

150302



Grease set suitable for drums 40 - 65 lbs

Composed by:

152801 Grease pump ratio=60:1

151016 Handle

153802 Lid Ø 12.60in

151004 Follower plate Ø 12.20in

150901 R2 1/4in hose - 10 ft length

100903 Grease gun with swivel joint





153101





Grease set suitable for drums 40 - 65 lbs

Composed like 150302 but without:

151004 Follower plate Ø 12.20in

			
150302	26.17	1.98	1
153101	25.23	1.98	1



150302



153201



Wheeled grease set suitable for drums 40 - 65 lbs

Composed by:

- 152801 Grease pump ratio=60:1
- 250037 2 wheels trolley
- 153802 Lid Ø 12.60in
- 151004 Follower plate Ø 12.20in
- 150901 R2 1/4in hose - 10 ft length
- 100903 Grease gun with swivel joint





150308




Wheeled grease set suitable for drums 40 - 65 lbs

Composed like 153201 but without:

- 151004 Follower plate Ø 12.20in

					
153201	39.69	1.98	1		Ø 10.24 - 12.60in
150308	36.76	1.98	1		



153301



Wheeled grease set suitable for keg 120 lbs

Composed by:

- 152805 Grease pump ratio=60:1
- 250038 2 wheels trolley
- 150509 Lid Ø 16.54in
- 151009 Follower plate Ø 15.75in
- 150901 R2 1/4in hose - 10 ft length
- 100903 Grease gun with swivel joint





150310




Wheeled grease set suitable for keg 120 lbs

Composed like 153301 but without:

- 151009 Follower plate Ø 15.75in

					
153301	44.76	2.79	1		Ø 14.57 - 16.54in
150310	39.25	2.79	1		



153401



Grease set suitable for drum 400 lbs

Composed by:





152802 Grease pump ratio=60:1

153803 Lid Ø 23.62in



151012 Follower plate Ø 23.23in

150901 R2 1/4in hose - 10 ft length

100903 Grease gun with swivel joint

			
153401	34.18	3.11	2
150305	34.99	3.11	2

Ø 22.05 - 23.62in



GREASE GR

150313



Wheeled grease set suitable for keg 120 lbs

Composed by:

152805 Grease pump ratio=60:1

250038 2 wheels trolley

150505 Lid Ø 15.55in

151006 Follower plate Ø 14.57in

150901 R2 1/4in hose - 10 ft length

100903 Grease gun with swivel joint





150312




Wheeled grease set suitable for keg 120 lbs

Composed like 150313 but without:

151006 Follower plate Ø 14.57in

			
150313	43.33	2.79	1
150312	38.52	2.79	1

Ø 13.39 - 15.16in





153501

153501



Wheeled grease set suitable for drum 400 lbs

Composed by:

152802 Grease pump ratio=60:1

250039 3 wheels trolley

153803 Lid Ø 23.62in

151012 Follower plate Ø 23.23in

150903 R2 1/4in hose - 16 ft length

100903 Grease gun with swivel joint




153501

99.379

7.064

2

Ø 22.05 - 23.62in



29.94in

31.52in

50.83in

GREASE
GR



150315

150315



Wheeled grease set suitable for drum 400 lbs with hose reel

Composed by:

152802 Grease pump ratio=60:1

250039 3 wheels trolley

153803 Lid Ø 23.62in

151012 Follower plate Ø 23.23in

150907 R2 1/4in hose - 5 ft length

100903 Gun with flexible pipe and fitting with triple-swivel joint

153601 Hose reel with R2 1/4in hose 32 ft length




150315

125.46

8.69

3

Ø 22.05 - 23.62in



29.94in

31.52in

50.83in

150316



Wheeled grease set suitable for drum 400 lbs

Composed by:

- 152802 Grease pump ratio=60:1
- 250066 4 wheels trolley
- 153803 Lid Ø 23.62in
- 151012 Follower plate Ø 23.23in
- 150903 R2 1/4in hose - 16 ft length
- 100903 Grease gun with swivel joint

			
150316	99.38	7.06	2



150316

150317




Wheeled grease set suitable for drum 400 lbs

Composed by:

- 152802 Grease pump ratio=60:1
- 250067 4 wheels trolley
- 153803 Lid Ø 23.62in
- 151012 Follower plate Ø 23.23in
- 150903 R2 1/4in hose - 16 ft length
- 100903 Gun with flexible pipe and fitting with triple-swivel joint

			
150317	125.46	8.69	3



150317

150318




Wheeled grease set suitable for drum 400 lbs with hose reel

Composed by:

- 152802 Grease pump ratio=60:1
- 250067 4 wheels trolley
- 153803 Lid Ø 23.62in
- 151012 Follower plate Ø 23.23in
- 150907 R2 1/4in hose - 5 ft length
- 100903 Gun with flexible pipe and fitting with triple-swivel joint
- 153601 Hose reel with R2 1/4in hose 32 ft length

			
150318	147.07	8.69	3



150318

WALL MOUNTED PNEUMATIC GREASE PUMP SETS



150401

150401



Wall mounted grease set suitable for drums 120 lbs

Composed by:

- 152805 Grease pump ratio=60:1
- 153601 Hose reel with R2 1/4in hose 32 ft length
- 150509 Lid Ø 16.54in
- 151009 Follower plate Ø 15.75in
- 150907 R2 1/4in hose - 5 ft length
- 100903 Gun with flexible pipe and fitting with triple-swivel joint
- 250006 Support for picking up drops

150402



Wall mounted grease set suitable for drums 120 lbs


Composed like 150401 but with:

- 150702 Hose reel with R2 1/4in hose 49 ft length



150401	74.97	4.31	4
150402	80.48	4.31	4

Ø 14.57 - 16.54in



150403

150403



Wall mounted grease set suitable for drum 400 lbs

Composed by:

- 152802 Grease pump ratio=60:1
- 153601 Hose reel with R2 1/4in hose 32 ft length
- 153803 Lid Ø 23.62in
- 151012 Follower plate Ø 23.23in
- 150907 R2 1/4in hose - 5 ft length
- 100903 Gun with flexible pipe and fitting with triple-swivel joint
- 250006 Support for picking up drops

150404



Wall mounted grease set suitable for drum 400 lbs


Composed like 150403 but with:

- 150702 Hose reel with R2 1/4in hose 49 ft length



150403	90.10	5.33	4
150404	94.15	5.33	4

Ø 22.05 - 23.62in



102304



Bucket Grease Pump - 15 lbs

Composed by:

Steel bucket with foot rest

Aluminum die cast pump

Swivel connector for hose

6ft high pressure rubber hose

Pistol handle fitted with Steel grease extension & professional coupler

Capacity 13lbs

Flow rate 0,30oz/stroke

Work pressure 3000 psi



102305



Bucket Grease Pump - 30 lbs

Composed by:

Steel bucket with foot rest

Aluminum die cast pump swivel for to connect hose

6ft high pressure rubber hose

Pistol handle fitted with Steel grease extension & professional coupler

Capacity 22lbs

Flow rate 0,30oz/stroke

Work pressure 3000 psi



102306



Wheeled Bucket Grease Pump - 30 lbs

Composed by:

Steel bucket with wheels

Aluminum die cast pump swivel for to connect hose

6ft high pressure rubber hose

Pistol handle fitted with Steel grease extension & professional coupler

Capacity 33lbs

Flow rate 0,30oz/stroke

Work pressure 3000 psi





152401

152401



Manual grease pump 35 lbs

Outlet grease pressure 5801 psi, 0.13 lbs delivery each 10 cycles of the lever

Composed by:


Mobile container 35 lbs

151001 Follower plate Ø 8.66in with spring

150003 Rubber hose R1 NPTF 1/4in - NPTF 10X1 6 ft length

150001 Outlet NPTM - NPTF 0.39x0.04in

150028 7.87in rigid pipe and 4-jaws coupling



152401

28.33

3.18

1

150602



Wheeled manual grease pump 35 lbs

Outlet grease pressure 5801 psi, 0.13 lbs delivery each 10 cycles of the lever

Composed by:


Wheeled container 35 lbs

151001 Follower plate Ø 8.66in with spring

150003 Rubber hose R1 NPTF 1/4in - NPTF 10X1 6 ft length

150001 Outlet NPTM - NPTF 0.39x0.04in

150028 7.87in rigid pipe and 4-jaws coupling



150602

31.53

3.18

1



150602

150603



Manual grease pump for drums of 30 lbs


Outlet grease pressure 5801 psi, 0.13 lbs delivery each 10 cycles of the lever

Composed by:

- 150502 Ø 11.02in drum lid
- 151002 Follower plate Ø 10.43in with spring
- 150003 Rubber hose R1 NPTF 1/4in - NPTF 10X1 6 ft length
- 150001 Outlet NPTM - NPTF 0.39x0.4in
- 150028 7.87in rigid pipe and 4-jaws coupling

			
150603	13.45	0.81	1

Ø 9.45 - 11.02in



150603

150604



Manual grease pump for drums of 40 - 65 lbs

Outlet grease pressure 5801 psi, 0.13 lbs delivery each 10 cycles of the lever

Composed by:

- 153802 Ø 12.60in drum lid
- 151004 Follower plate Ø 12.20in with spring
- 150003 Rubber hose R1 NPTF 1/4in - NPTF 10X1 6 ft length
- 150001 Outlet NPTM - NPTF 0.39x0.4in
- 150028 7.87in rigid pipe and 4-jaws coupling



150604

150608



Manual transfer grease pump for drums of 40 - 65 lbs

Suitable for filling manual grease pumps, 0.88 lbs delivery each 10 cycles of the lever

Composed by:

- 153802 Ø 12.60in drum lid
- 151004 Follower plate Ø 12.20in with spring
- 150002 Rigid connection 90° with adaptor Ø 0.35in



150608

150609







Manual transfer grease pump for drums of 40 - 65 lbs




Suitable for filling plants, 0.88 lbs delivery each 10 cycles of the lever

Composed by:

- 153802 Ø 12.60in drum lid
- 151004 Follower plate Ø 12.20in with spring
- 150034 R6 1/2in hose 6 ft length with level valve rigid end 30°
- 150916 Quick disconnect coupling NPTF 1/4in
- 150917 Quick disconnect coupling NPTM 1/4in

			
150604	14.44	0.81	1
150609	16.32	0.81	1
150608	14.00	0.81	1

Ø 10.24 - 12.60in



150609

HIGH PRESSURE MANUAL GREASE PUMPS



150606

150606



Manual grease pump for drums of 120 lbs .

Outlet grease pressure 5801 psi, 0.13 lbs delivery each 10 cycles of the lever

Composed by:

150509 Ø 16.54in drum lid




151009 Follower plate Ø 15.75in with spring

150003 Rubber hose R1 NPTF 1/4in - NPTF 10X1 6 ft length

150001 Outlet NPTM - NPTF 0.39x0.4in

150028 7.87in rigid pipe and 4-jaws coupling

			
150606	23.81	1.98	1



150610

150610



Manual transfer grease pump for drums of 120 lbs

Suitable for filling manual grease pumps, 0.88 lbs delivery each 10 cycles of the lever



Composed by:

150509 Ø 16.54in drum lid

151009 Follower plate Ø 15.75in with spring

150002 Rigid connection 90° with adaptor Ø 0.35in

			
150610	23.59	27.90	1



150611

150611



Manual transfer grease pump for drums of 120 lbs

Suitable for filling plants, 0.88 lbs delivery each 10 cycles of the lever

Composed by:

150509 Ø 16.54in drum lid



151009 Follower plate Ø 15.75in with spring

150034 R6 1/2in hose 6 ft length with level valve rigid end 30°

150916 Quick disconnect coupling NPTF 1/4in

150917 Quick disconnect coupling NPTM 1/4in

			
150611	25.80	27.90	1



150613



Wheeled manual transfer grease pump for drums of 40 - 65 lbs

Suitable for filling plants, 0.88 lbs delivery each 10 cycles of the lever

Composed by:

250036 2 wheels trolley


153802 Ø 12.60in drum lid

151004 Follower plate Ø 12.20in with spring

150034 R6 1/2in hose 6 ft length
with level valve rigid end 30°

150916 Quick disconnect coupling NPTF 1/4in

150917 Quick disconnect coupling NPTM 1/4in



150605



Wheeled manual grease pump for drums of 40 - 65 lbs

Outlet grease pressure 5801 psi, 0.13 lbs delivery each 10 cycles of the lever

Composed by:

250036 2 wheels trolley


153802 Ø 12.60in drum lid

151004 Follower plate Ø 12.20in with spring

150003 Rubber hose R1 NPTF 1/4in - NPTF 10X1 6 ft length

150001 Outlet NPTM - NPTF 0.39x0.4in

150028 7.87in rigid pipe and 4-jaws fitting



150612



Wheeled manual transfer grease pump for drums of 40 - 65 lbs

Suitable for filling manual grease pumps, 0.88 lbs delivery each 10 cycles of the lever


Composed by:

250036 2 wheels trolley

153802 Ø 12.60in drum lid

151004 Follower plate Ø 12.20in with spring

150002 Rigid connection 90° with adaptor Ø 0.35in





150607

150607



Wheeled manual grease pump for drums of 120 lbs

Outlet grease pressure 5801 psi, 0.13 lbs delivery each 10 cycles of the lever

Composed by:

250068 4 wheels trolley

150509 Ø 16.54in drum lid

151009 Follower plate Ø 15.75in with spring

150003 Rubber hose R1 NPTF 1/4in - NPTF 10X1 6 ft length

150001 Outlet NPTM - NPTF 0.39x0.4in

150028 7.87in rigid pipe and 4-jaws coupling



150614

150614



Wheeled manual transfer grease pump for drums of 120 lbs

Suitable for filling manual grease pumps, 0.88 lbs delivery each 10 cycles of the lever

Composed by:

250068 4 wheels trolley

150509 Ø 16.54in drum lid

151009 Follower plate Ø 15.75in with spring

150002 Rigid connection 90° with adaptor Ø 0.35in



150615

150615



Wheeled manual transfer grease pump for drums of 120 lbs

Suitable for filling plants, 0.88 lbs delivery each 10 cycles of the lever

Composed by:

250068 4 wheels trolley





150509 Ø 16.54in drum lid


151009 Follower plate Ø 15.75in with spring

150034 R6 1/2in hose 6 ft length with level valve rigid end 30°

150916 Quick disconnect coupling NPTF 1/4in

150917 Quick disconnect coupling NPTM 1/4in

				
150607	50.27	1.98	1	
150614	48.07	27.90	1	
150615	50.27	27.90	1	





100801

100801



Grease Control Valve Professional

Description

In steel construction, provides durability & longevity

With 360° Z swivel

Comes complete with 6in steel extension & heavy duty coupler

Inlet thread 1/4in NPTF

Outlet thread 1/8in NPTF

For operated grease pumps

Work pressure 7,500 PSI



100901

100901



Grease control gun without pipe and coupler

Description

Heavy duty in steel construction, provides durability & longevity.

Comes complete with 6in steel extension & coupler.

Pressure relief valve.

For operated air operated grease pumps.

With 360° Z swivel



100001



Z swivel connection

Max. work pressure : 12,000 PSI

NPTM 1/8in - NPTM 1/2in



101001



Grease Steel Extension

Description

Steel construction with bright zinc plated finish

High strength rolled threads on both ends

Available in straight & bent construction

Thread 1/8in NPTM

Length 6in work pressure 6,000 PSI



101002



Grease Steel Extension - 17.72in - Thread 1/8in NPTM

Description

Steel construction with bright zinc plated finish

High strength rolled threads on both ends

Available in straight & bent construction

Thread 1/8in NPTM

Length 18in work pressure 6,000 PSI



101101



Grease Hoses Heavy Duty - Length 11.81in - Thread 1/8in NPTM

Description

Inner tubing is poyamide with polyurethane sheathing, reinforced diagonally in highly tear resistant polyester

Heavy duty zinc plated end connections hydraulically crimped to the hose

Thread 1/8in NPTM

length 12in

Work pressure 13,775 PSI



101102



Grease Hoses Heavy Duty - Length 17.72in - Thread 1/8in NPTM

Description

Inner tubing is poyamide with polyurethane sheathing, reinforced diagonally in highly tear resistant polyester

Heavy duty zinc plated end connections hydraulically crimped to the hose

Thread 1/8in NPTM

length 18in

Work pressure 13,775 PSI



101103



Grease Hoses Heavy Duty - Length 19.69in - Thread 1/8in NPTM

Description

Inner tubing is poyamide with polyurethane sheathing, reinforced diagonally in highly tear resistant polyester

Heavy duty zinc plated end connections hydraulically crimped to the hose

Thread 1/8in NPTM

length 20in

Work pressure 13,775 PSI



151026

151026 Grease digital meter nozzle

Composed by:
Digital meter 4 digits
Triple-swivel joint
Rigid end + 4 jaws coupling
Not approved for public use

Technical data		151026
Inlet connection	NPTF	1/4in
Outlet connection	NPTF	10X1
Max working pressure	psi	7251.84
Burst pressure	psi	14503.68
Batch meter	digits	4
Totalizing meter in kg	digits	4
Working temperature	max F°	140.0
Battery life	months	24



103001

103001 Remote display out

Composed by:
In aluminum
Used with all pulser meters



101801

101801 Air Operated Grease Gun

Description
Heavy duty aluminum die cast head with internal bore precision honed for rapid action.
Complete with 6in steel extension & professional 4 jaw coupler.
Supply with cartridge loading, suction fill & filler pump loading.



101901

101901 High Power Air Operated Grease Gun

Description
Aluminum die cast construction with piston bore precision bore precision honed for rapid action
Air inlet threaded 1/4in NPTF, with a male quick coupler fitting
Complete with 9in steel extension & professional 4 jaw coupler
Capacity 14oz
Supply with cartridge loading, suction fill & filler pump loading

101201



Mini Pistol Grease Gun Deluxe

Description

Aluminum die cast head

Complete with 4in steel extension and 4 jaw coupler with ball check

Thread 1/8in NPTM

Capacity 3oz

Flor rate 0.60oz/40 strokes

Work pressure 3,000 PSI supply with cartridge loading



101201

101301



Push Type Grease Gun

Description

Steel body construction.

Complete with universal connector.

Capacity 5oz.

Supply with hand fill.



101301

101401



Standard Lever Grease Gun

Description

Body in aluminum, steel head.

Complete with a choice of 6in steel extension & 4 jaw coupler with ball check.

Thread 1/8in NPTM.

Supply with cartridge loading & suction fill



101401

101601



Pistol Grip Grease Gun Premium

Description

Robust aluminum die cast Grease gun head with bulk filler.

Complete with 12in high pressure flexible hose & professional 4 jaw coupler with ball check.

Supply with cartridge loading, suction fill & filler pump loading.



101601

101701



Lever Grease Gun Heavy Duty

Description

High tolerance aluminum die cast grease gun head.

Complete with a choice of 12in flexible hose extension & 4 jaw coupler with ball check.

Supply with cartridge loading, suction fill & filler pump loading.



101701

AUTOMATIC HOSE REEL FOR GREASE

Equipped with:

Synthetic black rubber hoses 2SC

Galvanized connections

Swivelling joint 90° galvanized

Polyurethane seals

Varnished fixed

Max. work pressure: 8702 PSI




GREASE
GR

Article	Hose length	Ø hose	Inlet-outlet
150716	Without hose	-	NPTM1/4in - NPTM1/4in
150717	Without hose	-	NPTM3/8in - NPTM3/8in
153601	30 ft	1/4in	NPTM1/4in - NPTM1/4in
150702	45 ft	1/4in	NPTM1/4in - NPTM1/4in
150703	30 ft	3/8in	NPTM3/8in - NPTM1/4in



GREASE
GR

Article	Hose length	Ø hose	Inlet-outlet
151022	Without hose	-	NPTM1/4in - NPTM1/4in
151023	Without hose	-	NPTM3/8in - NPTM3/8in
150704	55 ft	1/4in	NPTM1/4in - NPTM1/4in
153602	45 ft	3/8in	NPTM3/8in - NPTM1/4in



OVERALL DIMENSIONS FIXED

Mod.	A	B	C	D	E	F	G	H	lbs	ft ³	m ³
150702 - 150703 - 153601 - 150716 - 150717	6.22	4.72	6.61	7.56	3.74	17.72	15.75	17.13	27.56<43	1.62	1
150704 - 153602 - 151022 - 151023	6.22	4.72	6.61	7.56	3.74	18.90	18.11	19.69	36.38<50.72	2.12	1

AUTOMATIC HOSE REEL FOR GREASE



Equipped with:

Synthetic black rubber hoses 2SC

Galvanized connections

Swivelling joint 90° galvanized

Polyurethane seals

Varnished fixed


Max. work pressure: 8702 PSI



Article	Hose length	Ø hose	Inlet-outlet
151024	Without hose	-	NPTM3/8in - NPTM3/8in
150706	65 ft	3/8in	NPTM3/8in - NPTM1/4in
150707	80 ft	3/8in	NPTM3/8in - NPTM1/4in




Article	Hose length	Ø hose	Inlet-outlet
151025	Without hose	-	M3/8in - M3/8in
150708	95 ft	3/8in	M3/8in - M1/4in



OVERALL DIMENSIONS FIXED

Mod.	A	B	C	D	E	F	G	H	lbs	ft³	m³
150706 - 150707 - 151024	7.87	5.91	8.86	10.63	4.72	23.23	21.65	23.62	48.51<99.23	3.00	1
150708 - 151025	9.84	7.87	8.86	10.63	6.69	23.23	21.65	23.62	57.33<116.87	3.53	1



Equipped with:

Synthetic black rubber hoses 2SC

Galvanized connections

Swivelling joint 90° galvanized

Polyurethane seals

Varnished fixed

Max. work pressure: 8702 PSI



150712 - 150713 - 150711 - 150709 - 150710 - 150714 - 150715 50.49 < 65.82 2.12 1

GR

Article	Hose length	Ø hose	Inlet-outlet
150712	Without hose	-	NPTM1/4in - NPTM1/4in
150713	Without hose	-	NPTM3/8in - NPTM3/8in
150711	55 ft	1/4in	NPTM1/4in - NPTM1/4in
150709	30 ft	1/4in	NPTM1/4in - NPTM1/4in
150710	45 ft	1/4in	NPTM1/4in - NPTM1/4in
150714	30 ft	3/8in	NPTM3/8in - NPTM3/8in
150715	45 ft	3/8in	NPTM3/8in - NPTM3/8in



150901

Connection flexible hoses



Art.	Characteristics	Pressure	Burst	Length
150901	R2 1/4in NPTM - NPTF	W.P.1310 psi	5240 psi	9 ft
150902	R2 1/4in NPTM - NPTF	W.P.1310 psi	5240 psi	13 ft
150903	R2 1/4in NPTM - NPTF	W.P.1310 psi	5240 psi	16 ft
150904	R2 1/4in NPTM - NPTF	W.P.1310 psi	5240 psi	19 ft
150905	R2 1/4in NPTM - NPTF	W.P.1310 psi	5240 psi	24 ft
150906	R2 1/4in NPTM - NPTF	W.P.1310 psi	5240 psi	26 ft
150907	R2 1/4in NPTF - NPTF	W.P.1310 psi	5240 psi	4 ft
150908	R2 1/4in NPTF - NPTF	W.P.1310 psi	5240 psi	6 ft
150909	R2 3/8in NPTM - NPTF	W.P.1080 psi	4320 psi	9 ft
150910	R2 3/8in NPTM - NPTF	W.P.1080 psi	4320 psi	13 ft
150911	R2 3/8in NPTM - NPTF	W.P.1080 psi	4320 psi	16 ft
150912	R2 3/8in NPTF - NPTF	W.P.1080 psi	4320 psi	4 ft
150913	R2 3/8in NPTF - NPTF	W.P.1080 psi	4320 psi	6 ft



Synthetic black rubber hoses 2SC

Galvanized connections

Max. work pressure: 8702 PSI



Article	Hose lenght	Ø hose	Dimensions	Inlet-Outlet
150801	30 ft	1/4in	0.25 X 0.56	NPTF1/4in - NPTM1/4in
150802	45 ft	1/4in	0.25 X 0.56	NPTF1/4in - NPTM1/4in
150803	55 ft	1/4in	0.25 X 0.56	NPTF1/4in - NPTM1/4in
150804	30 ft	3/8in	0.38 X 0.72	NPTF3/8in - NPTM1/4in
150805	45 ft	3/8in	0.38 X 0.72	NPTF3/8in - NPTM1/4in
150806	65 ft	3/8in	0.38 X 0.72	NPTF3/8in - NPTM1/4in
150807	80 ft	3/8in	0.38 X 0.72	NPTF3/8in - NPTM1/4in
150808	95 ft	3/8in	0.38 X 0.72	NPTF3/8in - NPTM1/4in

FOLLOWER PLATE FOR PUMPS WITH SHANK Ø 1.18in



Art.	Ø Follower Plates	For drums	inside Ø
151001	8.66in	11 lbs	7.68 - 8.27in
151002	10.43in	26 - 35 lbs	9.45 - 10.24in
151003	11.42in	35 - 44 lbs	9.84 - 11.02in
151004	12.2in	40 - 66 lbs	10.63 - 11.81in
151005	13.39in	44 - 66 lbs	11.81 - 12.99in
151006	14.57in	66 - 110 lbs	13.19 - 14.17in
151009	15.75in	110 - 132 lbs	14.17 - 15.75in
151012	23.23in	397 - 485 lbs	21.26 - 22.83in



FOLLOWER PLATE FOR INDUSTRIAL PUMPS WITH SHANK Ø 1.77in



Art.	Ø Follower Plates	For drums	inside Ø
151007	14.57in	66 - 110 lbs	13.19 - 14.17in
151010	15.75in	110 - 132 lbs	14.17 - 15.75in
151013	23.23in	397 - 485 lbs	21.26 - 22.83in



FOLLOWER PLATE FOR INDUSTRIAL PUMPS WITH SHANK Ø 1.97in



Art.	Ø Follower Plates	For drums	inside Ø
151008	14.57in	66 - 110 lbs	13.19 - 14.17in
151011	15.75in	110 - 132 lbs	14.17 - 15.75in
151014	23.23in	397 - 485 lbs	21.26 - 22.83in



FOLLOWER PLATE



Art.	Ø Follower Plates	For drums	inside Ø
103701	13.62in	40 lbs	12.12 - 13.62in
103702	14.25in	120 lbs	12.75 - 14.25in
103703	23.25in	400 lbs	21.75 - 23.25in



It is advisable to use always the follower plate, it is very important of ambient temperature is low and when high viscosity grease is used. Because of the depression created by the pump, the plate is attracted towards the bottom of the drum by atmospheric pressure. It pushing the grease into the pump and avoids air cavities. Also it removes the grease remaining on the walls down to the bottom of the drums.

DRUM COVER

LID FOR PUMPS WITH SHANK Ø 1.18in

GR



Art.	Ø lid	For drums	outside Ø
150501	8.86in	11 lbs	7.87 - 8.86in
150502	11.02in	26 - 35 lbs	9.45 - 11.02in
153802	12.6in	40 - 66 lbs	10.24 - 12.6in
150504	13.78in	44 - 66 lbs	11.81 - 13.78in
150505	15.55in	66 - 110 lbs	13.39 - 15.55in
150509	16.54in	110 - 132 lbs	14.57 - 16.54in
153803	23.62in	397 - 485 lbs	21.65 - 23.62in

LID FOR INDUSTRIAL PUMPS WITH SHANK Ø 1.77in

GR



Art.	Ø lid	For drums	outside Ø
150506	15.55in	66 - 110 lbs	13.39 - 15.55in
150510	16.54in	110 - 132 lbs	14.57 - 16.54in
153801	23.62in	397 - 485 lbs	21.65 - 23.62in

LID FOR INDUSTRIAL PUMPS WITH SHANK Ø 1.97in

GR



Art.	Ø lid	For drums	outside Ø
150507	15.55in	66 - 110 lbs	13.39 - 15.55in
150511	16.54in	110 - 132 lbs	14.57 - 16.54in
150515	23.62in	397 - 485 lbs	21.65 - 23.62in

LID FOR INDUSTRIAL PUMPS WITH MUFF 2in F

GR



Art.	Ø lid	For drums	outside Ø
150508	15.55in	66 - 110 lbs	13.39 - 15.55in
150512	16.54in	110 - 132 lbs	14.57 - 16.54in
150516	23.62in	397 - 485 lbs	21.65 - 23.62in

Suitable for the application of the threaded ring fixing pumps.

The drum lid is available in different diameters to fit drums from 11 to 441 lbs. A handle provides an easy way to the drum. It keeps the pump in vertical position in order to assure a perfect working.

150007



Support cabinet for 4 hose reels

Composed by:

Basin with grate for picking up drops

Support with grate

Dimensions 43.82x19.69 H.98.43in




150007

423.36

32.85

1



150007

The hose reels aren't included in the cabinet

150008



Support cabinet for 6 hose reels

Composed by:

Basin with grate for picking up drops

Support with grate

Dimensions 61.02x19.69 H.98.43in



150008

474.08

32.85

1



150008

These structures will be supplied only and exclusively inrey colour

Fixed cabinets that offer an independent working station. They allow an optimal placing in every working environment (factories and repair shops) allowing to operate in a clean and safe way and without wasting of lubricant oils for different uses.

This fixed cabinets can be connected to a centralized distribution system and became individual working station.



150012

150012



Double fixed bracket varnished

For closed hose reels Mod. 150709 - 150710 - 150711 - 150712 - 150713
150714 - 150715



150013

150013



Rotary support varnished

For fixed hose reels Mod. 150702 - 150703 - 150716 - 150717 - 153602 -
150704 - 150709 - 150710 - 150711 - 150712 - 150713 - 150714 - 150715



150014

150014



Rotary support varnished

For fixed hose reels Mod. 150706 - 150707



150015


150015




Rotary support varnished

For fixed hose reels Mod. 150708


OVERALL DIMENSION BRACKET




150702 - 150703
150716 - 150717
153602 - 150704



150706
150707



150708



150709 - 150710
150711 - 150712
150713 - 150714
150715

150009



Panel support 2 hose reels

For the application hose reels Mod. 150702 - 150703 - 150716 - 150717 - 153602 - 150704 - 150706 - 150707

Dimensions 23.23x153.66x25.61in



150009

150010



Panel support 3 hose reels

For the application hose reels Mod. 150702 - 150703 - 150716 - 150717 - 153602 - 150704 - 150706 - 150707

Dimensions 33.86x153.66x25.61in



150010

150011



Panel support 4 hose reels

For the application hose reels Mod. 150702 - 150703 - 150716 - 150717 - 153602 - 150704 - 150706 - 150707

Dimensions 43.82x153.66x25.61in



150011



150009	19.40	7.63	1
150010	26.46	11.06	1
150011	33.74	14.13	1

102201



Heavy Duty Grease Gun Holder

Description

Heavy duty grease gun holder, designed specially for use on farm & construction equipment, trailers, tractor other automobiles in high vibrations environments

Sturdy all steel construction with a 4 bolt design for easy & secure mounting
Heavy duty spring - works with guns with 2,1/4in diam.



102201